

Solidfood

DRY FOOD HOSE



Código	Diameter		Working pressure		Burst pressure		Weight nominal	Min. bending radius	Length max	
	Inside	Outside	bar	psi	bar	psi			m	ft
IGH092W	90	103	6	87	18	261	2,92	710	60	200
IGH101W	102	114	6	87	18	261	2,88	815	60	200
IGH102W	102	118	6	87	18	261	3,89	815	60	200

Other length on request.

ES

Materiales secos y abrasivos

- **Normativa:** FDA tit.21 art.177.2600 alimentos secos y abrasivos. Libre de FTALATOS
- **Aplicación:** manguera de pared blanda con anti abrasivo blanco FDA, adecuado para transportar con sistemas neumáticos alimentos abrasivos, polvo y granos de PVC que no deben mancharse.
- **Temperatura:** de -30°C à +70°C.

Construcción

- **Tubo interior:** caucho NR/SBR blanco, liso, resistente al polvo abrasivo y a los alimentos.
- **Refuerzo:** capas sintéticas de alta resistencia e hilos de cobre incrustados.
- **Cobertura:** goma EPDM negra, lisa (acabado envolvente), eléctricamente conductora de caucho.
- **Marcaje:** banda de color rojo/blanco "GASSÓ SOLIDFOOD...".
- **Disponible bajo pedido:** 1.Otros diámetros 2.Cobertura en otros colores 3.Otras presiones de trabajo

ENG

For dry and abrasive food

- **Regulations:** FDA tit.21 item 177.2600 for dry abrasive foods PHTALATES free.
- **Application:** soft-walled hose with FDA white anti-abrasive, suitable for conveying with pneumatic systems abrasive foodstuffs, powder and PVC grains that must not stain.
- **Temperature:** from -30°C (-22°F) to +70°C (+158°F).

Construction

- **Inner tube:** white NR/SBR rubber, smooth, resistant to abrasive dust and foodstuffs.
- **Reinforcement:** high strength synthetic layers and embedded copper wires.
- **Cover:** black, smooth EPDM rubber (wrap-around finish), electrically conductive rubber.
- **Marking:** red/white band "GASSÓ SOLIDFOOD".
- **Also available upon request.** 1.Different diameters 2.Hose cover in different colours 3.Different working pressures.

