

SPRING FLEX

PVC hose with embedded galvanised steel wire. Smooth inside and outside wall.

Suction and impulsion pumping of liquids in general. Alcoholic liquids up to 20%.

Non-toxic and for alimentary use according to 1935/2004 European Directive and 10/2011 Regulation for A, B, C).

Vacuum and pressure values correspond to $23\pm 2^{\circ}\text{C}$ working temperatures (ISO 291).

Manguera de PVC flexible con espiral de acero galvanizado, pared interior y exterior lisa.

Aspiración e impulsión de líquidos alimentarios, alcoholes hasta el 20%.

Atóxica y de uso alimentario, SIN O-FHTALATOS (Directiva Europea 1935/2004 y Reg. 10/2011 para Simulantes A, B, C).

Los valores de vacío y presión corresponden a temperaturas de trabajo de $23\pm 2^{\circ}\text{C}$ (ISO291).



TECHNICAL SPECIFICATIONS · ESPECIFICACIONES TÉCNICAS

Inside: Smooth · Interior: superficie lisa en PVC

Outside: Smooth · Exterior: liso en PVC

Inner reinforcement: Anti-shock PVC · Refuerzo interior: PVC antichoque

Temperature: -10°C to $+60^{\circ}\text{C}$ · Temperatura: -10°C a $+60^{\circ}\text{C}$

Available colours · Colores disponibles

CODE CÓDIGO	Ø INS (mm) Ø INT (mm)	Ø EXT (mm) Ø EXT (mm)	LENGTH (m) LONGITUD (m)	2669WEIGHT (g/m) PESO (g/m)	PRESSURE (bar) PRESIÓN (bar)	VACUUM (mH2O) VACIO (mH2O)
720020	20	26	50	304	9	8
720025	25	32	50	442	9	8
720030	30	37	50	504	9	8
720032	32	39	50	528	9	8
720035	35	43	50	620	7	8
720038	38	45	50	662	7	8
720040	40	49	50	786	7	7
720045	45	54	50	920	6	7
720050	50	60	50	1.100	6	7
720055	55	66	50	1.218	6	7
720060	60	71	50	1.398	6	7
720065	65	77	50	1.606	4,5	7
720070	70	83	50	1.778	4,5	7
720075	75	88	50	1.904	4	7
720080	80	93	50	2.116	3,5	7
720090	90*	104	30	2.669	3	7

* Diameters marked with (*) are subject to availability. Other diameters and colors are available upon request.

* Los diámetros con (*) son bajo demanda. Otros diámetros y colores consultar.